




 Dekeghel nv
 Overnelleweg 29
 B-1740 Ternat
 Tel +32(0)24606022
 Fax +32(0)26692222
 www.dekeghel.be info@dekeghel.be

PASSAGE MINIMUM FOUR DEMONTE 850x2150

TYPE FOUR	DIMENSIONS CHAMBRE CUISSON DxC		A	B	F	G	CALORIES GIGLEUR GPH	TUYAUX POUR BRULEUR	PUISS. ELECTR.	CONSUM. HORAIRE M ³ GAS /H	P0IDS KG
SCT1-3C/3,4	0.70 X 1.60	3,4	1,37	2,26	0,77	∅160	35.000 1.00	1" GAS	1.5 KW	2,2	1800
SCT1-3C/4,2	0.70 X 2.00	4,2	1,37	2,66	0,77	∅160	40.000 1.20				
SCT2-3C/6	1.20 X 1.60	5,8	1,85	2,26	0,77	∅200	55.000 1.25	1"1/4 GAS	2.5 KW	3,5	2460
SCT2-3C/7	1.20 X 2.00	7,2	1,85	2,66	0,77	∅200	60.000 1.50				
SCT3-3C/9	1.80 X 1.60	9,0	2,46	2,26	0,84	∅200	70.000 2.00				
SCT3-3C/11	1.80 X 2.00	11,0	2,46	2,66	0,84	∅200	90.000 2.25				
SCT3-3C/13	1.80 X 2.50	13.5	2,46	3,16	0,84	∅200	95.000 3.00	1"1/2 GAS	5.0 KW	6,1	3910

POS.	DESCRIPTION
6	EVACUATION DES VAPEURS
5	EVACUATION DES FUMES
4	ARRIVEE-RETOUR GAZ/MAZOUT (A TERRE)
3	EVACUATION EAU (A TERRE)
2	ARRIVEE EAU (H.2150 - ∅1/2")
1	ENERGIE ELECTRIQUE (H.2150)

CARACTERISTIQUE TECHNIQUE FOUR CICLOTERMiques 3 C.

DATA 09.05.05	UISTO .	DATA 19.11.01
BOLL. 1045	DIS. SA.	DIS.N° POS.332-2


 DISEGNO DI PROPRIETA' RISERVATA E NON PUO' ESSERE RIPRODOTTO O MOSTRATO A TERZI AI SENSI DI LEGGE